



2026 RULES

6 SHOOTERS

Updated 3/1/2026

1. MODELS:

1. 2011 2010 and older, V-6 powered, General Motors, Ford Motor Company or Mopar production front wheel drive passenger cars with a factory minimum wheelbase of 103". Convertibles not allowed. (Some examples would be: GM: Century, LeSabre, Cutlass, Grand Am, Grand Prix, Ford: Taurus, Sable, etc. Mopar: Intrepid, Concord) Foreign models are NOT allowed. No modifications or alterations except as specifically allowed in these rules.
2. VIN must be visible and legible.

2. Breakout Rule:

1. Tomah Sparta Breakout Time- 18.000 *The Breakout time may be adjusted for the sake of competition Ex. New pavement etc.*
2. The 6 Shooter class at Tomah Sparta Speedway will have a Breakout Rule - faster than a pre-determined lap time will result in disqualification and black flagged from the heat race and or qualifying after receiving a one warning for a violation over the Raceciever. For feature events two warnings will be issued. An automatic black flag will be issued with a lap faster than 17.700. 17.699 will be black flagged. If there is a Breakout on the last lap(White Flag Lap) it will result in a DQ for that event

3. BODY:

1. Complete full body cars only with no trimming or other modifications to the body. No gutting of doors, hood or trunk allowed. All interior upholstery, except for driver's seat and driver side door panel or padding, must be removed. The dash and instrument cluster must remain intact. All airbags must be deactivated. All exterior lights, brake lights, lenses and reflectors must be removed. Third brake light must be operable. Light holes may be covered with sheet steel to improve the cars appearance. Front and rear firewalls and floor must be complete, and all holes covered with sheet steel. Sun roof openings must be closed off with sheet steel

4. BUMPERS:

1. Stock bumpers for car only, and must be secured with chains or welded to prevent them from falling off. Exposed bumper ends must be capped and not have sharp edges.
2. Chains required on bumpers

5. GLASS:

1. All side windows and rear window must be removed. Broken glass must be cleaned from inside the car before arriving at the speedway. The original windshield must be used, severely cracked may require stock replacement Lexan replacement allowed (with tech approval) with a minimum thickness of .090" with minimum of three support bars in front of driver. One stock inside mirror only; all outside mirrors must be removed.

6. ROLL CAGE:

1. A two-point roll cage is recommended. Must be made of minimum 1 3/4" OD mild steel tubing with a minimum wall thickness of .090". No weld elbows or fittings. Only mandrel bends are allowed. Cage design is a main hoop with a diagonal brace, positioned behind the driver's seat, extending from the floor to the roof, and extending the width of the driver's compartment. This main hoop should be braced from the top of the hoop, down and rearward to the lower rear section of what was the back seat area; two braces, one on each side. No bars are allowed to pass through the front or rear firewall. No bars may extend beyond the contour of the body.
2. Door plate must pass 6" on each side of the door seam and 14' tall minimum Must be secure with 8, grade 8 carriage bolts 7/16" in diameter, at least 4 mounted to something structural with locking nuts
3. Cars with cage DOES NOT NEED the Door Plate

7. ENGINE:

1. V-6 engines only with a maximum displacement of 3.8 liters. The engine must be original or an exact replacement as offered in make and model of your car. The engine must remain completely stock. No turbo-chargers or super-chargers.

8. ELECTRICAL:

1. 12-volt electrical system only. Battery must remain in stock location. Battery must be secured with a minimum of 1/8" thick x 1" wide steel strap, and 5/16" bolts. OEM stock sensors and computers only. OEM stock computer chips only. No tuner, performance or programmable chips allowed. OEM stock wiring harness must be used. No re-wiring without an official's approval.

9. COOLING SYSTEM:

1. Stock radiator, or any other radiator that fits in the stock mounts. The A/C condenser and compressor may be removed, but all other A/C components must remain. 2 electric cooling fans may be used. A coolant recovery bottle is mandatory.
2. Water only in the cooling system. NO ANTIFREEZE. Antifreeze is strictly prohibited and carries a \$100 fine.

10. EXHAUST:

1. **Mufflers are Mandatory** and are not to be tampered with or hollowed out. Sound level must be less than 100 db and must meet local & county ordinance requirements where measured.
2. 2 1/2" O.D. maximum. Must exit behind the driver and under car. **If exhaust exits out under the side of car, pipe may not extend past the skirts of body.**

11. FUEL SYSTEM:

1. Fuel pump must have no power when car is off. No fuel lines allowed in driver's compartment.
2. Fuel Tank: The stock fuel tank may be used if it is located forward of the rear axle; stock fuel fill must remain. A fuel tank (fuel cell or 6.6-gallon marine tank) may be mounted in the trunk, secured with minimum of 1/8" x 1" steel straps and 3/8" bolts.

12. DRIVE LINE:

1. Completely stock driveline only.

13. SUSPENSION:

1. The suspension system must remain completely stock. The springs may not be heated or cut. OEM stock for your make and model, springs, control arms, bushings, shocks, struts, spindles, etc. only. Up to 1-inch of camber will be allowed in the RF tire only. Anything exceeding that amount will be disqualified.

14. STEERING:

1. The steering system must remain completely stock. Alternatively, removable steering wheel is allowed with a collapsible steering shaft.

15. BRAKES:

1. Stock brakes for that make and model only must remain functional on all four corners. Rotor and/or caliper size may not be changed. Stock master cylinder only. Anti-lock braking system may remain functional. Brake bias adjusting devices are not allowed.

16. TIRES/ WHEELS

1. Tires: All 4 tires must be the same size and aspect ratio, examples: 215/70R15, or 225/60R16. Steel belted DOT radial tires only, 60, 65, 70, or 75 series.
2. **No made for racing tires, Race tires, or Performance Street Tires allowed.**
3. **Tires must not exceed \$75 MSRP. Management may claim any tire for \$65.**
4. All tire brands and products must be T or H rated and meet approval from management. Minimum durometer reading is 60. Minimum UTQG rating 380.
5. Chemical treatment of tires (softening) is not permitted and if found guilty will result in the disqualification from the event and loss of prize money and points. Drivers guilty of altering and/or chemical treatment of tires may also be suspended. If a driver is found altering and/or chemical treatment of tires on the last night of competition, he/she will be disqualified for that night of points and prize money and deducted of all points from the previous night of competition.
6. **If tires are bought online, they must be purchased from a location/site that is available for all drivers to purchase from**
7. Wheels: Stock wheels only; must be stock size and width for that make and model of car only, steel wheels are recommended. Maximum width of 6.5" for all wheels. Stock offsets for your car should be utilized. All 4 must be the same size; 14", 15" or 16".

TIRE SIZE GUIDE



17. WEIGHT & GROUND CLEARANCE:

1. No ballast allowed. Stock ground clearance must be maintained. Cars appearing too low will be subject to disqualification.

18. SEAT:

1. The original seat or racing seat can be used. The seat back must be locked into position.

19. SAFETY:

1. A driver's window net is required, with release at top front of net. The center of the steering wheel must be padded.
2. Racing seat belts are recommended.
3. A fully charged dial type fire extinguisher, minimum 2 lb. BC, securely mounted, within the driver's reach, is required.
4. Helmet required, minimum DOT standard, Snell SA recommended
5. Eye protection and racing suit recommended. Long sleeve shirts, long pants, closed toed shoes and gloves required, No Nylon or similar material allowed.

20. CLAIM RULE:

1. Management has the right to claim any car at any time. The Claim amount is \$1000 for a 6 Shooter. Drivers may keep seat belts and racing seat.
2. If you refuse a legal claim, you will forfeit any points, trophies and prize money for the entire season. Car and driver will be ineligible to compete for the remainder of the season.

21. Car Numbers:

1. Numbers at least 18-inches high on both sides and on roof readable from left side, along with 6-inch high numbers in top right corner of windshield and on back of trunk on right side above tail light are required.
2. No spray painted or "duct" tape numbers.

22. MISCELANOUS:

1. This class is designed as a true entry level division.
2. **Transponders are mandatory** and located approximately 20" (inches) in from rear bumper outside the car mounted on the spare tire hump under the car



facing downward with a clear view to the track surface.

Transponders Available at the track for rent.

3. No two-way radio communication allowed. This class will utilize transponder scoring.
4. Race lines up will be based on season points or qualifying.
5. **Scanners/Raceceiver required. Frequency is 454.000.**
6. Have fun.

END OF 6 SHOOTER RULES SECTION